




CSTFE...DO2RS

TERMINALE A SNODO RILUBRIFICABILE

BALL-JOINT END WITH GREASE NIPPLE



Codice Code	ØP	Z	S	D1	S1	L	F	LF min	FC (kN)	kg
**05.CSTFE.917D20	17	69	14	46	11.0	92.0	M16x2	36	21.2	0,19
**05.CSTFE.920D20	20	78	16	53	13.0	104,5	M20x1.5	43	30.0	0,31
05.CSTFE.925D20	25	94	20	64	17.0	126.0	M24x2	53	48.0	0,56
05.CSTFE.930D20	30	110	22	73	19.0	146,5	M30x2	65	62.0	0,89
05.CSTFE.935D20	35	140	25	82	21.0	181.0	M36x3	82	80.0	1,40
05.CSTFE.940D20	40	150	28	92	23.0	196.0	M39x3	86	100.0	1,80
05.CSTFE.945D20	45	163	32	102	27.0	218.0	M42x3	94	127.0	2,60
05.CSTFE.950D20	50	185	35	112	30.0	241.0	M45x3	106	156.0	3,40
05.CSTFE.960D20	60	210	44	135	38.0	277,5	M52x3	115	245.0	5,90
05.CSTFE.970D20	70	235	49	160	42.0	315.0	M56x4	125	315.0	8,20
05.CSTFE.980D20	80	270	55	180	47.0	360.0	M64x4	140	400.0	13.10

FC = CARICO DINAMICO AMMESSO - MAX DYNAMIC LOAD

** = RILUBRIFICABILE MEDIANTE FORO - LUBRICATING HOLE IN THE HEAD

MATERIALE: ACCIAIO ISO 12240-4 SERIE E TIPO M / MATERIAL: STEEL ISO 12240-4 SERIES E TYPE M