



CSTFI...DO2RS


TERMINALE A SNODO RILUBRIFICABILE
BALL-JOINT END WITH GREASE NIPPLE



TFI 6-20 DO/DO2RS



TFI 25-80 DO/DO2RS



Codice Code	ØP	Z	S	D1	S1	L	F	LF min	FC (kN)	kg
**05.CSTFI.817D20	17	67	14	46	11.0	90.0	M16x2	34	21.2	0,22
**05.CSTFI.820D20	20	77	16	53	13.0	103,5	M20x1.5	40	30.0	0,35
05.CSTFI.825D20	25	94	20	64	17.0	126.0	M24x2	48	48.0	0,64
05.CSTFI.830D20	30	110	22	73	19.0	146,5	M30x2	56	62.0	0,93
05.CSTFI.835D20	35	125	25	82	21.0	166.0	M36x3	60	80.0	1,30
05.CSTFI.840D20	40	142	28	92	23.0	188.0	M39x3	67	100.0	2,01
05.CSTFI.845D20	45	145	32	102	27.0	196.0	M42x3	65	127.0	2,50
05.CSTFI.850D20	50	160	35	112	30.0	216.0	M45x3	69	156.0	3,50
05.CSTFI.860D20	60	175	44	135	38.0	242.0	M52x3	73	245.0	5,50
05.CSTFI.870D20	70	200	49	160	42.0	280.0	M56x4	80	315.0	8,60
05.CSTFI.880D20	80	230	55	180	47.0	320.0	M64x4	85	400.0	12.00

FC = CARICO DINAMICO AMMESSO - MAX DYNAMIC LOAD

** = RILUBRIFICABILE MEDIANTE FORO - LUBRICATING HOLE IN THE HEAD

MATERIALE: ACCIAIO ISO 12240-4 SERIE E TIPO F / MATERIAL: STEEL ISO 12240-4 SERIES E TYPE F